





Magnetic grippers

HGR-SQ-100-FL-RH-G-F

Article number: TPGC100378

Product Features

Description Magnetic gripper Article number TPGC100378 **Product key** HGR-SQ-100-FL-RH-G-F Size 100 mm Specific application Suitable for high temperatures **Switching** Pneumatic Advised working load 400 N (under ideal conditions - with safety factor 3 acc. EN13155) Max. tear off force 1200 N (under ideal conditions - Graph: see Downloads tab - Factors influencing lifting capacity: see /solutions/magnetic-handling) Min. advised sheet thickness 3 mm Interface/connection dim's Threaded hole M6 (8x), Threaded hole M10 **Connections** Pneumatic: G1/8" (2x) **Material housing** Aluminium, AISI316L (SS 1.4404) (screw cap) Surface treatment/finishing Nickel plated Colour Grey Min./max. ambient temperature 0 to 120 °C **Switching pressure** Max. 4 bar **Magnetic system** 8 Permanent magnet poles Neodymium GSN-38EH, Br 12,600 gauss (at 20 °C), Tmax. 180 °C **Magnet quality** Depth 100 mm Width 100 mm Height 70 mm Weight 1.5 kg **Type** High temp. Air consumption 1.352 l/cycle (1x up, 1x down)